

INFERNO OUTDOOR

SOUND BARRIER DATA SHEET

- ⇒ renders the protected area uninhabitable & forces intruders to retreat immediately.
- ⇒ significantly reduces costs of intrusions by limiting the intruders' time inside.
- ⇒ generates an utterly intolerable sound spectrum, broadcast at 125dB.
- ⇒ compatible with all existing alarm systems, simple to retrofit and install.
- ⇒ environmentally shielded (IP54) to permit trouble-free operation in demanding conditions
- ⇒ ultra-high Swedish quality & durability.

The Outdoor is an environmentally shielded version of the all conquering Intenso. It is equipped with a protective membrane that effectively seals the unit against ingress of water, dust and other contaminants. It is thus ideally suited to installations where it will be exposed to harsh environmental conditions. It is typically installed undercover, above external doorways often targeted as a soft point of access. It is also deployed in situations where airborne particles such as dust and moisture have the potential to interfere with normal operation.

Inferno sound barriers protect premises and objects that demand a heightened level of security. They are typically deployed in situations where conventional security equipment has/will fail to provide sufficient protection. The intruder depends on the "window of opportunity" that exists between detection and arrival of security

personnel. By rendering an area uninhabitable, the sound barrier destroys this window and with it, the intruder's ability to inflict damage and loss.

The Outdoor's patented sound generator has recently been optimized, resulting in substantially improved runtime and a significant reduction in power consumption. Requiring only a 12V feed to maintain the internal battery, it can operate without mains power. Designed, manufactured and assembled in Sweden to ultra-high standards, the Outdoor is encased in a rugged aluminium and plated-steel shell, making it both durable and attractive.



TECHNICAL SUMMARY

Protective capability:	Up to 70m ²
Dimensions: (mm)	685 x 106 x 40
Weight:	1.7kg
Frequency range:	2 - 5kHz
Acoustic effect:	125 - 127db (A)
Battery backup:	9.6V, 1800mAh, Ni-MH
Battery lifetime:	3 years
Power consumption:	12-16V DC, <150mA
Runtime:	> 30 minutes
Temperature range:	-10 to +60°C
IP class:	IP54



SONIC SECURITY™

Forcing the intruder to depart immediately, empty handed and without confrontation, is the ultimate solution in any intrusion.

Inferno - intolerable to intruders.